

NPRG036
XML Technologies



Lecture 3
XPath

2. 3. 2020

Author: **Irena Holubová**
Lecturer: **Martin Svoboda**

<http://www.ksi.mff.cuni.cz/~svoboda/courses/192-NPRG036/>

Lecture Outline

□ XPath

- Data model
 - Path expressions
 - Axes, node tests, predicates
-

Query Languages for XML Data

- Aims: querying, views, transformations, actualization, ...
 - Since 1998 XML-QL, XQL, ...
 - The development stabilized in W3C in languages XSLT, XPath, XQuery
 - XSLT is a language for data transformation
 - Exploits XPath for targeting parts of XML document
 - Has XML syntax
 - XQuery is more suitable for querying – user-oriented
 - Exploits XPath for targeting parts of XML document
 - Today: XPath 1.0
 - Note: XPath 2.0 \subset XQuery
-

What is XPath?

- Basic language for querying XML data
 - Selecting parts of XML documents
 - The idea resembles navigation in a file system
 - XPath does not have XML syntax
 - XPath is exploited in multiple other XML technologies
 - XSLT, XQuery, XML Schema, XPointer, ...
-

XPath Data Model

```
<?xml version="1.0"?>
<!DOCTYPE order SYSTEM "order.dtd">
<order date="10/10/2008" status="confirmed">
  <customer number="C992">Steve J.</customer>
  <items>
    <item code="48282811">
      <amount>5</amount>
      <price>22</price>
    </item>
    <item code="929118813">
      <amount>1</amount>
      <price>91934</price>
      <color>blue</color>
    </item>
  </items>
</order>
```

XPath Data Model

```
<?xml version="1.0"?>
<!DOCTYPE order SYSTEM "order.dtd">
<order date="10/10/2008" status="confirmed">
  <customer number="C992">Steve J.</customer>
  <items>
    <item code="48282811">
      <amount>5</amount>
      <price>22</price>
    </item>
    <item code="929118813">
      <amount>1</amount>
      <price>91934</price>
      <color>blue</color>
    </item>
  </items>
</order>
```

document


XPath Data Model

```
<?xml version="1.0"?>
<!DOCTYPE order SYSTEM "order.dtd">
<order date="10/10/2008" status="confirmed">
  <customer number="C992">Steve J.</customer>
  <items>
    <item code="48282811">
      <amount>5</amount>
      <price>22</price>
    </item>
    <item code="929118813">
      <amount>1</amount>
      <price>91934</price>
      <color>blue</color>
    </item>
  </items>
</order>
```

document


XPath Data Model

```
<?xml version="1.0"?>
<!DOCTYPE order SYSTEM "order.dtd">
<order date="10/10/2008" status="confirmed">
  <customer number="C992">Steve J.</customer>
  <items>
    <item code="48282811">
      <amount>5</amount>
      <price>22</price>
    </item>
    <item code="929118813">
      <amount>1</amount>
      <price>91934</price>
      <color>blue</color>
    </item>
  </items>
</order>
```




XPath Data Model

```
<?xml version="1.0"?>
<!DOCTYPE order SYSTEM "order.dtd">
<order date="10/10/2008" status="confirmed">
  <customer number="C992">Steve J.</customer>
  <items>
    <item code="48282811">
      <amount>5</amount>
      <price>22</price>
    </item>
    <item code="929118813">
      <amount>1</amount>
      <price>91934</price>
      <color>blue</color>
    </item>
  </items>
</order>
```




XPath Data Model

```
<?xml version="1.0"?>
<!DOCTYPE order SYSTEM "order.dtd">
<order date="10/10/2008" status="confirmed">
  <customer number="C992">Steve J.</customer>
  <items>
    <item code="48282811">
      <amount>5</amount>
      <price>22</price>
    </item>
    <item code="929118813">
      <amount>1</amount>
      <price>91934</price>
      <color>blue</color>
    </item>
  </items>
</order>
```



XPath Data Model



XPath Data Model

□ Types of nodes in the model

- Root node
- Element node
- Text node
- Attribute node
- Comment
- Processing instruction
- Namespace

□ What is not included: CDATA section, entity reference, DTD

XPath Data Model


□ Specifics

- Attributes are not a part of list of child nodes of a node
 - Namespace declarations are not considered as attributes, but special types of nodes
 - `xmlns:bib="..."`
 - The root node does not represent root element but the whole document
 - Root element is represented as a child of root node
-


XPath Expression

- XPath expression is a **path**
 - Path consists of **steps**
 - Absolute path:
 - `/Step1/Step2/.../StepN`
 - Relative path:
 - `Step1/Step2/.../StepN`
-

XPath Expressions – Examples




XPath Expressions – Examples




XPath Expressions – Examples

`/order/items/item`




XPath Expressions – Examples

```
/order/items/item/@code
```




XPath Expressions – Examples

```
/order/items/item/price/text()
```




XPath Expressions – Examples

```
/order/items/item/color
```




XPath Expressions – Examples

`/order/customer/name`



XPath Expressions – Examples

`/order/item-list/item`




XPath Expressions – Examples

`price/text()`

- A **relative** path itself cannot be evaluated separately
 - It does not make sense, because we do not know where to start
 - The input must involve both the relative path and one or more nodes of XML documents where the evaluation should start
 - so-called **context set**
-


XPath Expressions – Examples

`price/text()`




XPath Expressions – Examples

`price/text()`




XPath Expressions – Examples

`price/text()`



XPath Expressions – Examples

`price/text()`



Evaluation of XPath Expression

- Let P be an XPath path
 - Let C be the context set of nodes for evaluation of P
 - If P is absolute, then C contains the root node of the document
 - If P is relative, then C must be specified explicitly
 - If P is empty, then the result of evaluation corresponds to C
 - Else, P is evaluated with regards to C as follows:
 - Let S be its first step and P' is the rest of the path, i.e. $P = S/P'$
 - $C' = \{ \}$
 - For each node u from C evaluate S and add the result to C'
 - Evaluate P' with regard to C'
-

XPath Paths Formally

- XPath step is formally the following expression:

```
axis::node-test predicate1 ... predicateN
```

- Axis, node test and list of predicates
 - Predicates are optional
- So far we saw only node tests
 - The list of predicates was empty
 - Axes were abbreviated

???

XPath Axes

```
axis::node-test predicate1 ... predicateN
```

- Axis specifies the relation of nodes selected in this step with regard to each node **u** from context set **C**

```
child
```


- Selected nodes are child nodes of node **u**
- Most common axis

```
/order/customer ↔  
/child::order/child::customer
```

abbreviation


XPath Axis **self**

- The selected node is **u** itself




XPath Axis **parent**

- Parent node of node **u**




XPath Axis ancestor

- All ancestor nodes of node **u**
 - All nodes on the path from **u** to root node




XPath Axis ancestor-or-self

- All ancestor nodes of node u including u




XPath Axis **child**

- All child nodes of node **u**




XPath Axis descendant

- All descendant nodes of node **u**




XPath Axis descendant

- All descendant nodes of node **u**




XPath Axis descendant-or-self

- All descendant nodes of node u including u




Tree Traversal




XPath Axis preceding-sibling

- All siblings of **u** which precede it in tree traversal




XPath Axis preceding

- All nodes which precede **u** in tree traversal
 - Except for ancestors




XPath Axis following-sibling

- All siblings of **u** which follow it in tree traversal




XPath Axis following

- All nodes which follow **u** in tree traversal
 - Except for ancestors



XPath Axis **attribute**


- All attributes of node **u**



XPath Axis namespace

- All namespace declarations of node **u**
 - Similarly to axis attribute it selects nodes of a special type
-

All XPath Axes



XPath Node Test

```
axis::node-test predicate1 ... predicateN
```

- Tests nodes selected by the axis
 - Node type, node name
-


XPath Node Test

```
axis::node() predicate1 ... predicateN
```

- All nodes selected by the axis
-

XPath Node Test

`descendant::node()`




XPath Node Test

```
axis::text() predicate1 ... predicateN
```

- All text nodes selected by the axis
-

XPath Node Test

`descendant::text()`



XPath Node Test

```
axis::* predicate1 ... predicateN
```


- All nodes selected by the axis which have a name
 - Name can have an element or an attribute
 - Note: there exists no axis that enables to selected elements and attributes at the same time

```
axis::name predicate1 ... predicateN
```

- All nodes with the specified **name**
-

XPath Node Test

descendant::*



XPath Node Test

- ❑ `axis::comment()`
 - ❑ `axis::processing-instruction()`
 - ❑ `axis::processing-instruction("php")`
-

XPath Axes and Node Test Abbreviations

- For the most commonly used axes and node tests

```
.../... <=> .../child::...  
.../@... <=> .../attribute::...  
.../. ... <=> .../self::node() ...  
.../. ... <=> .../parent::node() ...  
...//... <=> .../descendant-or-self::node()/...
```

- `//customer` **selects all elements** `customer` in XML document



!!!

XPath Predicates

```
axis::node-test predicate1 ... predicateN
```

- A predicate enables to specify advanced conditions for nodes which were selected by the axis and node test
 - For context node **u** we find all nodes selected by the axis from node **u**
 - On input we put those which satisfy node test and all predicates

```
predicate ::= '[' condition ']'  
condition ::= not(' condition ') |  
              condition and condition |  
              condition or condition
```

```
[condition1][condition2] <=> [condition1 and condition2]
```



XPath Predicates

- Predicate condition can be a **relative** XPath path **P**
 - For node **u** it returns **true** if the set of nodes returned by path **P** from **u** is non-empty
 - Predicated condition can be an **absolute** XPath path **P**
 - It returns **true** if the set of nodes returned by path **P** is non-empty
-

XPath Predicates

`//item[@code]`


Relative path: `attribute::code`



XPath Predicates


`//item[price]`

Relative path: `child::price`




XPath Predicates

```
//item[../../@status]
```




XPath Predicates

```
//item[ancestor::order/@status]
```



XPath Predicates

```
//order[@status]//item
```




XPath Predicates

- The condition can involve comparison of two operands
 - Operands are XPath expressions
 - XPath path, value, ...
 - Operators are = != < > <= >=
 - String value of node
 - Attribute – normalized value
 - Element – concatenation of text nodes in its subtree
-


XPath Predicates

```
//item[color = "blue"]
```




XPath Predicates

```
//item[price > 30]
```




XPath Predicates

```
//order[@status = "confirmed"]//item
```



XPath Predicates

□ Operators = != ...


- Operands are sets of values/nodes 
- Evaluated as **true** if there exists a value/node in the left operand and a value/node in the right operand for which the operator evaluates as **true**

□ Consequences:

- Expression with = and != can return the same result!
 - `x="foo"` is **not** the same as `not (x!="foo")`
 - There exists a node in **x** with string value `foo`
 - All nodes in **x** have string value `foo`
-


XPath Predicates

```
//item[color = "blue"]
```



XPath Predicates

```
//item[color != "blue"]
```




Built-in Functions

□ Testing of position

- Each node in a context set has a position
 - Determined by its position in document and the (direction of a) particular path
 - `position()`
 - Returns the position of node in a context set
 - `last()`
 - Returns the number of nodes in a context set
-


Built-in Functions

```
//items/item[position() = 1]
```




Built-in Functions

```
//items/item[1]
```




Built-in Functions

```
//items/item[position() = last()]
```



Built-in Functions

```
//items/item[last()]
```




Built-in Functions

`count(expression)`

- Returns the number of results given by `expression`
-

Built-in Functions

```
//items[count(item) > 2]
```



Built-in Functions

- `+`, `-`, `*`, `div`, `mod`
 - `name()`, `id()`
 - `concat()`, `starts-with()`,
`contains()`, `substring-after()`,
`substring-before()`, `substring()`,
...
 - `sum()`, `floor()`, `ceiling()`, ...
-